

# STAINLESS STEEL TANKER

## SPECIFICATIONS

**TYPE:** STRAIGHT ROUND, DOT 407 SPEC

**CAPACITY:** 7000 GALLONS, PLUS 2% **COMPARTMENT:** SINGLE

**COMMODITY:** UNSPECIFIED FLUIDS DESIGN  
25 PSI INTERNAL

**PRESSURE:** 38 PSIG HYDROSTATIC TEST

**TEMP:** 180 DEG F MAXIMUM

**SHELL:** 10 GA, 316L STAINLESS STEEL, 2B FINISH

**HEAD:** 10 GA, 316L STAINLESS STEEL, 2B FINISH  
ASME F&D

**BAFFLE:** NONE

**WELDS:** INTERNAL- GROUND FLUSH, EXTERNAL-  
AS WELDED

**STIFFENER RINGS:** EXTERNAL CHANNEL, SOLID WELDED

**MANWAY:** 20" MANHOLE, 6 HOLD DOWN, HYPALON  
GASKET IN LID, NEAR CENTER OF TANK, HINGED TO  
FRONT

**CLEANOUTS:** 2-3" MALE PIPE NIPPLE WITH STAINLESS  
STEEL ON TOP CENTER LINE, WITHIN 10" FROM EACH  
HEAD SEAM OVER TURN PROTECTION: SPILL DAM AT TOP  
MANWAY WITH DRAIN HOSE, INCLUDES RELIEF VALVE  
AND VAPOR RECOVERY VALVE

**EMERGENCY:** BETTS 4" X 3" HYDRAULIC OPERATED  
EXTERNAL

**VALVE:** PUMP LOCATED AT REAR, FUSIBLE/ FRANGIBLE  
BREAKAWAY LOCATED AT FRONT

**OUTLET VALVE:** BETTS 3" QRB HYDROLET W/ 90  
DEG OUTLET, 3" SPOOL PIPING AS SHORT AS POSSIBLE,  
3" SS CAM LOCK & CAP WITH RETAINER CABLE



**VAPOR RECOVERY:** 3" X 2 TEE STYLE HYDRAULIC  
OPERATED VALVE SEQUENCED WITH EMERGENCY  
VALVE, PRESSURE GAUGE INSTALLED IN TANK  
CONNECTION PIPE, TOP CONNECTION WITH BALL  
VALVE, CAM AND LOCK CAP, DRIVERS SIDE  
CONNECTION AT REAR WITH PRESSURE GAUGE, BALL  
VALVE, CAM AND LOCK CAP

**RELIEF'S:** DOT SPECIFICATION, FORT VALE STAINLESS  
STEEL PRESSURE/VACUUM RELIEF VALVE, LOCATED IN  
SPILL DAM WITH AIR KIT AND GAUGE

**LEVEL GAUGE:** GARNET 808P2 LEVEL GAUGE WITH 316  
FLOAT

**THERMOMETER:** 0-3000 DEG INSTALLED ON SIDE  
HEATING STAINLESS STEEL CHANNELS FULL LENGTH, 150  
PSI MAWP

**SYSTEM:** STREAM AND IN TRANSIT, INLET AND OUTLET  
AT FRONT

**INSULATION:** 6" FIBERGLASS COMPRESSED TO 5"



FOR MORE INFO : [NTERENTS.COM](http://NTERENTS.COM) | 888.213.7950

# STAINLESS STEEL TANKER

## SPECIFICATIONS

**JACKETING:** 22 GA BA/SS, LAPPED SEAMS, 18 GA #4 FINISH LOCK SEAM JACKET ON HEADS ADDITIONAL ALL BOLSTERS, LONG MEMBERS, SUB FRAME, SUSPENSION  
**COMPONENTS:** BOX, BUMPER, HOSE TUBE MOUNTS AND FENDER MOUNTS CONSTRUCTED FROM STAINLESS STEEL

**HOSE TUBE:** 2-8" X 21' HOSE TUBE, ONE EACH SIDE

**LADDER:** BOLT ON LADDER TO SPILL BOX WITH TOP PLATFORM STEP AND GRAB HANDLES (NO SIDE HAND RAIL) INSTALLED ON CURB SIDE, 12" WIDE WALKWAY TO CLEANOUTS, 12 WIDE ON 3 INCHES OF SPILL DAM

**LIGHTS:** FULL DOT LIGHTS , LED SEALED LIGHTS, HARNESS AND JUNCTION BOX WITH TERMINAL STRIP

**AXLES:** 25,000 LB ROUND WITH OUTBOARD DRUMS

**SUSPENSIONS:** HUTCH 9700 WITH 3 LEAF HIGH ARCH SPRINGS

**WHEELS:** 10 HOLE STEEL, HUB PILOT

**TIRES:** 11.00 X 24.5 RADIAL

**BRAKES:** 16 1/2 X 7 WITH SPRING PARKING, AUTO SLACKS, WABCO 4S-2M ABS SYSTEM, UPPER 5/16" BOLSTER PLATE, BOLT ON ADJUSTABLE

**COUPLER:** 49" TRUCK 5TH WHEEL HEIGHT

**LANDING LEGS:** 2 SPEED, HEAVY DUTY, HIGH CAPACITY LIFT

**BUMPER:** HEAVY DUTY PER DOT REQUIREMENTS

**FENDERS:** 3/4 FENDERS ON FRONT, FULL ON REAR

**MUD FLAPS:** ANTI SAIL

**PLACARDS:** 4- SIDE IN PLACARD FRAMES



**NATIONAL  
TANK & EQUIPMENT**

FOR MORE INFO : [NTERENTS.COM](http://NTERENTS.COM) | 888.213.7950