



Standard Specification

Tare: 27,000 lbs.
Capacity: 17,826 gallons (430 BBL)
Walls/Roof: 1/4" A36 plate
Floor: 1/4" A36 plate
Floor Rails: 12" x 20.7# channel
X-Members: 1/4" A36 plate
Side Stakes: 3/16" A36 plate formed
Axle: 77.5" track, 22,500 lbs. capacity
Tires: 11R22.5
Manways: (3) 22" (curb)
Valves: (2) 4" Butterfly (front); (1) 4" Drain (front);
(1) 4" Drain with handle (rear)
Blind Flange: (2) 4" (rear)
Fill Line: (1) 3" with nipple and cap (rear)
Sign: (1) 47 x 47 (curb); (1) 47 x 47 (street)
Weir: (1) Under weir & over weir
Weld: AWS D1.1
OSHA: 1910 Subpart D

Blast

- Interior: SSPC-SP-10 (near white)
- Exterior: SSPC-SP-6 (commercial blast)

Paint

- Interior: Epoxyphenolic 100% solid 20.0 MILS D.F.T.
- Exterior: Finish coat polyurethane 4.0 to 5.0 D.F.T.

Add-Ons

- 10 x 50 Berm
- Liquid level gauge
- Hose bridge
- High level alarm
- Site tube



Mechanical Dimensions

