



Standard Specification

Tare: 26,000 lbs.
Capacity: 21,000 gallons (500 BBL)
Walls/Roof: 1/4" A36 plate
Floor: 1/4" A36 plate
Floor Rails: 12" x 20.7# channel
X-Members: 1/4" A36 plate; (1) removable cross member (roof)
Side Stakes: 3/16" A36 plate formed
Axle: 77.5" track, 22,500 lbs. capacity
Tires: 11R22.5
Manways: (1) 22" (front); (1) 22" (curb)
Valves: (2) 4" Memi butterfly (front); (2) 4" Memi butterfly (rear); (2) 6" Memi butterfly (front); (1) 4" Drain (front); (1) 4" Drain w/handle (rear)
Vent: (2) 6" (rear)
Sign: (1) 48 x 54 (curb); (1) 48 x 54 (street)
Weir: (1) Under weir; (2) Over weir
Weld: AWS D1.1
OSHA: 1910 Subpart D

Blast

- Interior: SSPC-SP-10 (near white)
- Exterior: SSPC-SP-6 (commercial blast)

Paint

- Interior: Epoxyphenolic 100% solid 20.0 MILS D.F.T.
- Exterior: Finish coat polyurethane 3.0 to 4.0 D.F.T.

Add-Ons

- 10 x 50 Berm
- Liquid level gauge
- Hose bridge
- High level alarm
- Site tube



Mechanical Dimensions

